




RICO
YOU WILL SEE



RICO GmbH
D-87437 Kempten
Dieselstraße 15
Tel. +49 (0) 831 / 5716 - 0
Fax +49 (0) 831 / 5716 - 226
Mail info@rico-gmbh.de
Web www.rico-gmbh.de



Your RICO-Partner

TINY | PC.2

RICO
YOU WILL SEE.



Push-Rod System

Universally usable for property drainage

100 m

from 30 mm

EN

TINY | PC.2

Product Features

- Mobile push-rod system, suitable from Ø 30 mm to 300 mm
- Depending on the requirements various cameras can be used
- With either 60 m or 100 m push-rod cable
- Light, compact and easy to transport
- Folding PC case with an anti-glare multi-touch monitor, suitable for daylight, 26,4 cm/10,4 inches
- Integrated industrial PC with SSD hard disk drive
- Inclusive basic software WinCan ProTouch Lite
- Optionally with complete sewer TV inspection software
- **Made in Germany**




Fast & Comfortable Data Transfer

- Wi-Fi for wireless data transfer
- Bluetooth, e. g. for connecting a mouse, keyboard, etc.
- USB for connecting devices, e. g. printer, hard disk drive, etc.



Ergonomic & Easy to Use

- Height-adjustable, detachable control unit, horizontally and vertically adjustable (Grafik 360°)
- Transportable stainless steel frame
- Easy operation



Laser Measurement

- Integrated parallel lasers inside the camera head enable
- Diameter measurement
 - Deformation measurement
 - Damage measurement



EASY | EXACT | EFFICIENT

RICO sets standards in compactness, mobility and functionality

Technical Data

PC monitor	<ul style="list-style-type: none"> • 26,4 cm/10,4 inches • Capacitive multi-touch monitor • Suitable for daylight, anti-glare • Brightness: 800 cd/m² • Resolution: 1024 x 768 Pixel • Contrast: 900:1 	USB	• 2 x 3.0
Processor	• Intel® Core™ i5	WLAN	• IEEE 802.11 b/g/n
Hard disk drive	• SSD 120 GB	Analogue video output	• BNC
Internal memory	• DDR3 4 GB	Digital video output	• HDMI
Operating system	• Windows 8.1 Professional 64 Bit	Data interface (meter counter)	• USB (B)
		Power supply	• 110 to 240 V AC 50 to 60 Hz
		Weight	• 24 kg (without camera)



Kompatibel mit folgenden Kameras

- MINI, Ø 30 – 100 mm
- VERTICA 30, Ø 40 – 200 mm
- VERTICA 40, Ø 50 – 250 mm
- SR50 (pan and tilt camera), Ø 70 – 300 mm

Optional

- Various guide, brush and roller skids for the operation in different pipe diameters
- Power station for working independently of the mains
- 20 m connection cable between PC case and reel
- Mobility Box with video input for using the PC case separately

